


Electron Generator Arrays

ELECTROGEN™



Features

- Uniform high density electron flux
- Cold ionization source
- Excellent stability
- Custom shapes and sizes
- Low maintenance
- Fine emission control
- Applications support

Applications:

- Electron impact ionization source
- Fluorescent display screens
- Electron scrub sources
- Sample discharge for SEMs
- Mass spectrometry
- Residual Gas Analysis

Photonis patented **ELECTROGEN™ Electron Generator Arrays (EGAs)** consist of millions of precision glass tubes fused together to produce a uniform and mechanically rigid structure. They are processed such that, when a voltage is applied across the thickness, each pore produces a beam of electrons. With each of the millions of pores producing electron, the resultant electron flux is extremely uniform and dense.


An EGA does not require any warm-up time, and will not burn out. No heat-up and stabilization period is required. EGAs require much less maintenance than filament sources while providing much higher current densities. EGAs are available with emission areas in a variety of shapes and sizes from 4 to 150 mm diameter.

In mass spectrometry applications, EGAs can be used as the electron source in electron impact ionization sources. This new technology has the advantage of performing as a cold ionization source. In conventional sources the heat from the filament often causes pyrolytic effects. Pyrolytic effects occur when the heat generated by the filament chemically changes the unknown substances to be identified. Once ionized, this altered substance does not produce an ion representing the original substance. The use of a cold electron source eliminates this concern.

Flux Density

Typically, a single EGA will produce an electron flux density exceeding 1.0×10^{-10} A/cm². By using a Chevron™ or Z- Stack configuration, current densities up to as 2.0×10^{-5} A/cm² can be reached. The flux density is uniform to within 10 % across the entire emission area.

Stability



PHOTONIS EGAs provide a uniform electron flux over a wider area than conventional filament sources.

EGA Assemblies

PHOTONIS EGA can be provided in an easy to use assembly. A standard configuration consists of Electron Generator Plates assembled in single, Chevron™, or Zstack assemblies mounted in stainless steel hardware with mounting holes and electrical connection terminals. Sizes range from 4 to 150 mm diameter. Custom sizes are also available. These assemblies are available with optional output grids for electron energy discrimination.

PHOTONIS USA, Inc. 660 Main St, Sturbridge, MA USA 01566
 T: +1 (508) 347 4000 or Toll Free US/Canada (800) 648 1800
 E: sales@usa.photonis.com W: www.photonis.com

PHOTONIS
 Scientific Detectors

The information furnished is believed to be accurate and reliable, but is not guaranteed and is subject to change without notice. No liability is assumed by PHOTONIS for its use. Performance data represents typical characteristics as individual product performance may vary. Customers should verify that they have the most current PHOTONIS product information before placing orders. No claims or warranties are made as to the application of PHOTONIS products. Pictures may not be considered as contractually binding. This document may not be reproduced, in whole or in part, without the prior written consent of PHOTONIS.